

# kuželový závit

Written by Administrator

Tuesday, 30 August 2011 12:10 -

**Závitové očka** DIN EN 24230

**R** Kuželový závit R, ISO-7/1

Odstředěná materiál: **HSS**

Použitelná látka: **-**

Těsnost: **1,7**

Průměr	P	h <sub>1</sub> , h <sub>2</sub>	h	h <sub>1</sub> + h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>
R 10	1,27	0,635	0,635	1,27	0,635	0,635	0,635
R 12,5	1,58	0,79	0,79	1,58	0,79	0,79	0,79
R 16	2,0	1,0	1,0	2,0	1,0	1,0	1,0
R 20	2,54	1,27	1,27	2,54	1,27	1,27	1,27
R 25	3,18	1,59	1,59	3,18	1,59	1,59	1,59

**Závitové očka** DIN EN 22568

**Pg** Závit na instalační rourky ocelové, DIN-40430

Odstředěná materiál: **HSS**

Použitelná látka: **-**

Těsnost: **1,75 P**

Průměr	P	h <sub>1</sub> , h <sub>2</sub>	h	h <sub>1</sub> + h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>
Pg 10	1,27	0,635	0,635	1,27	0,635	0,635	0,635
Pg 12,5	1,58	0,79	0,79	1,58	0,79	0,79	0,79
Pg 16	2,0	1,0	1,0	2,0	1,0	1,0	1,0
Pg 20	2,54	1,27	1,27	2,54	1,27	1,27	1,27
Pg 25	3,18	1,59	1,59	3,18	1,59	1,59	1,59

**Závitové očka** NF-E-74.001

**M** Metrický závit

Odstředěná materiál: **HSS** **LT**

Použitelná látka: **HSS** **FG**

Těsnost: **1,75 P** **1,75 P**

Průměr	P	h <sub>1</sub> , h <sub>2</sub>	h	h <sub>1</sub> + h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>	h <sub>1</sub> - h <sub>2</sub>
M 0,5	0,5	0,25	0,25	0,5	0,25	0,25	0,25
M 0,6	0,6	0,3	0,3	0,6	0,3	0,3	0,3
M 0,8	0,8	0,4	0,4	0,8	0,4	0,4	0,4
M 1,0	1,0	0,5	0,5	1,0	0,5	0,5	0,5
M 1,25	1,25	0,625	0,625	1,25	0,625	0,625	0,625
M 1,6	1,6	0,8	0,8	1,6	0,8	0,8	0,8
M 2,0	2,0	1,0	1,0	2,0	1,0	1,0	1,0
M 2,5	2,5	1,25	1,25	2,5	1,25	1,25	1,25
M 3,2	3,2	1,6	1,6	3,2	1,6	1,6	1,6
M 4,0	4,0	2,0	2,0	4,0	2,0	2,0	2,0
M 5,0	5,0	2,5	2,5	5,0	2,5	2,5	2,5
M 6,3	6,3	3,15	3,15	6,3	3,15	3,15	3,15
M 8,0	8,0	4,0	4,0	8,0	4,0	4,0	4,0
M 10	10	5,0	5,0	10	5,0	5,0	5,0
M 12,5	12,5	6,25	6,25	12,5	6,25	6,25	6,25
M 16	16	8,0	8,0	16	8,0	8,0	8,0
M 20	20	10,0	10,0	20	10,0	10,0	10,0
M 25	25	12,5	12,5	25	12,5	12,5	12,5
M 32	32	16,0	16,0	32	16,0	16,0	16,0
M 40	40	20,0	20,0	40	20,0	20,0	20,0
M 50	50	25,0	25,0	50	25,0	25,0	25,0
M 63	63	31,5	31,5	63	31,5	31,5	31,5
M 80	80	40,0	40,0	80	40,0	40,0	40,0
M 100	100	50,0	50,0	100	50,0	50,0	50,0
M 125	125	62,5	62,5	125	62,5	62,5	62,5
M 160	160	80,0	80,0	160	80,0	80,0	80,0
M 200	200	100,0	100,0	200	100,0	100,0	100,0
M 250	250	125,0	125,0	250	125,0	125,0	125,0
M 315	315	157,5	157,5	315	157,5	157,5	157,5
M 400	400	200,0	200,0	400	200,0	200,0	200,0
M 500	500	250,0	250,0	500	250,0	250,0	250,0
M 630	630	315,0	315,0	630	315,0	315,0	315,0
M 800	800	400,0	400,0	800	400,0	400,0	400,0
M 1000	1000	500,0	500,0	1000	500,0	500,0	500,0

NTV - náhradní, s.r.o., Parková 26, 017 01, Dolná, Tel./fax: +421(0)496 61 16, 496 49 41, e-mail: ntv@pg.sk, www.ntv.sk